

SENS211VIR

Ultimate Day & Night Outdoor IR Dome Camera



Features

- High Resolution (Color: 560 TV Lines, B/W: 700 TV Lines)
- 1/3" SONY High Sensitivity SUPER HAD CCD II
- New SENS DSP
- 2.8 ~ 11 mm Auto Iris Vari-Focal Lens
- Weather & Vandal Resistant Housing (IP66)
- 24 IR LED (100ft IR Range)
- Day & Night (Sens Up)
- Mechanically Switching IR cut filter
- Digital Noise Reduction (DNR)
- DC12V (680mA) or AC 24V (Dual Voltage Support)

Specification

CCD	1/3" SONY High Sensitivity CCD II
Effective Pixel	768 (H) x 494 (V)
Scanning System	2:1 Interlaced
Resolution	More than 560 TV Lines (Color), More than 700 TV Lines (B/W)
Lens	2.8 ~ 11 mm DC Auto-Iris Lens
Backlight	BLC/HLC/OFF Selectable
Weatherproof	Yes, IP66
Video Output	1.0 Vp-p / 75
S/N (Y Signal)	52dB (AGC Off, Weight ON)
IR Range	100 ft
Sens-Up	AUTO / FIXED / OFF (Selectable Limit x2 ~ x256)
Gain Control	LOW / HIGH / OFF Selectable
White Balance	ATW / AWC / MANUAL / OUTDOOR / INDOOR
On Screen Display	Available
Digital Noise Reduction	ON / OFF (1~32) LEVEL ADJUSTABLE
Motion Detection	ON / OFF (8 ZONE, ALARM Output)
Freeze	ON / OFF
Sharpness	ON / OFF
D N Selection	COLOR / Black & White / AUTO / EXT (Built in DC Motor Drive)
Digital Image Stabilization	ON / OFF
Privacy	ON / OFF (8 ZONES)
Flip (V -REV), Mirror (H-REV)	ON / OFF
Power Supply	DC12V (680mA) / AC 24V
Operating Temp / Humidity	14 °F ~ 122 °F / 30 ~ 90% RH
Dimensions	5.91" (W) x 3.94 (D)
Weight	1.32 lb